

Picture

TECHNICAL PROPERTIES



DA-100

POWER SUPPLY:	150-250VAC
Operating Frequency:	50/60HZ
Measure Range:	0.2-200A
Accessorry :	AT100
Protection Class:	IP44
Display:	8mm 3 dight
Weight:	164g
Package:	100 pcs/ctn



DAV-100

POWER SUPPLY:	150-250VAC
Operating Frequency:	50/60HZ
Measure Range:	0.2-200A 150-250VAC
Accessorry :	AT100
Protection Class:	IP44
Display:	8mm 3 dight
Weight:	169g
Package:	100 pcs/ctn



DIN-U

POWER SUPPLY:	150-250VAC
Operating Frequency:	50/60HZ
Measure Range:	2.5-420VAC
Accessorry :	NONE
Protection Class:	IP44
Display:	8mm 3 dight
Weight:	147g
Package:	100 pcs/ctn



DIN-F

POWER SUPPLY:	150-250VAC
Operating Frequency:	50/60HZ
Measure Range:	2.5-420VAC
Accessorry :	NONE
Protection Class:	IP44
Display:	8mm 3 dight
Weight:	147g
Package:	100 pcs/ctn



DVF

POWER SUPPLY:	150-250VAC
Operating Frequency:	50/60HZ
Measure Range:	30-70hz 2.5-420VAC
Accessorry :	NONE
Protection Class:	IP44
Display:	8mm 3 dight
Weight:	147g
Package:	100 pcs/ctn

Dimensions and technical parameters

