

UL 1028 Hook-up Wire 连接线



AWM 1028 AWG VW-1 105°C 600V E234411 BETTER C AWM I A 105°C 600V FT1

PRODUCT DESCRIPTION

- Rated temperature: 105°C
Rated voltage: 600V
- Reference standard: UL Subject 758, UL1581 & CSA C22.2 No.210.2
- Tinned or bare, stranded or solid copper conductor, 22-6 AWG
- Colour-coded lead free PVC insulation
- Uniform insulation thickness to ensure easy stripping and cutting
- Passes UL VW-1 & CSA FT1 vertical flame test

APPLICATION

For internal wiring of electronic and electrical equipment

说明

- 额定温度: 105°C
额定电压: 600V
- 标准: UL758, UL1581及
CSA C22.2 No. 210.2
- 导体使用22-6AWG 单根或绞合裸铜
或镀锡铜线
- 无铅聚氯乙烯绝缘
- 绝缘厚度均匀, 方便剥皮及剪裁
- 通过UL VW-1及CSA FT1垂直耐燃测试

应用

用于电子、电器设备内部连线

Conductor 导体			Insulation 绝缘		Standard Put-Up	Maximum Resistance at 20°C
AWG	NO. /mm	Dia	Nom. Thick.	Nom. Dia.	标准长度 M/Coil	最大导体电阻 Ω/km
线规	线数/线径	外径 mm	绝缘厚度 mm	外径 mm		
22	17/0.16	0.76	1.143	3.15±0.10	610	57.52
20	26/0.16	0.94	1.143	3.3±0.10	610	37.61
18	41/0.16	1.18	1.143	3.6±0.10	610	23.85
16	26/0.254	1.49	1.143	3.9±0.10	305	15.06
14	41/0.254	1.87	1.143	4.3±0.10	305	9.46
12	65/0.254	2.36	1.143	4.8±0.10	305	6.3
10	105/0.254	3.00	1.143	5.4±0.15	305	4.13
8	165/0.254	3.76	1.143	6.2±0.10	305	
6	262/0.254	4.74	1.524	7.2±0.15	305	