

UL 21014



AWM 21014 VW-1 80°C 300V E234411 BETTER C

AWM I A 80°C 300V FT1

PRODUCT DESCRIPTION

- Rated temperature: 80°C
Rated voltage: 300V
- Reference standard: UL subject 758, UL1581 & CSA C22.2 No.210.2
- Stranded, bare or tinned copper conductor 20-17AWG
- Colour-coded PVC insulation
- Lead free PVC jacket
- Passes UL VW-1& CSA FT1 vertical flame test

APPLICATION

For internal wiring and external interconnection of electronic equipment

说明

- 额定温度：80°C
额定电压：300V
- 标准：UL758，UL1581及 CSA C22.2 No. 210.2
- 导体使用绞合裸铜或镀锡铜线 20-17AWG
- 聚氯乙烯绝缘
- 无铅聚氯乙烯护套
- 通过UL VW-1及CSA FT1垂直耐燃测试

应用

用于电子设备内部及外部连线

Cores	Conductor 导体		insulation 绝缘		Jacket 外被		Maximum Resistance at 20°C 最大导体电阻 Ω/km
	AWG	NO. /mm	Nom. Thick.	Nom. Dia	Jacket thickness	Jacket. Dia	
芯线数	线规	线数/线径	绝缘厚度 mm	外径 mm	外被厚度 mm	外径 mm	
2	20	26/0.16	0.61	2.2	0.61	5.65	37.61
2	18	41/0.16	0.61	2.4	0.61	6.00	23.85