

UL 1011 Hook-up Wire 连接线



有 AWM 1011 AWG VW-1 80°C 600V E234411 BETTER c有 AWM I A 80°C 600V FT1

PRODUCT DESCRIPTION

- Rated temperature: 105°C
Rated voltage: 600V
- Reference standard: UL Subject 758, UL1581 & CSA C22.2 No.210
- Tinned or bare, stranded or solid copper conductor, 30-3/0 AWG
- Colour-coded lead free PVC insulation
- Uniform insulation thickness to ensure easy stripping and cutting
- Passes UL VW-1 & CSA FT1 vertical flame test

APPLICATION

For internal wiring of electronic and electrical equipment

说明

- 额定温度：80°C
额定电压：600V
- 标准：UL758，UL1581及
CSA C22.2 No. 210
- 导体使用30-3/0AWG 单根或绞合裸铜或镀锡铜线
- 无铅聚氯乙烯绝缘
- 绝缘厚度均匀, 方便剥皮及剪裁
- 通过UL VW-1及CSA FT1垂直耐燃测试

应用

用於电子、电器设备内部连线

Conductor 导体			Insulation 绝缘		Standard Put-Up	Maximum Resistance at 20°C
AWG	NO. /mm	Dia	Nom. Thick.	Nom. Dia.	标准长度 M/Coil	最大导体电阻 Ω/km
线规	线数/线径	外径 mm	绝缘厚度 mm	外径 mm		
26	7/0.16	0.49	0.76	2.05±0.10	610	139.73
24	11/0.16	0.61	0.76	2.20±0.10	610	88.89
22	17/0.16	0.76	0.76	2.40±0.10	610	57.52
20	26/0.16	0.94	0.76	2.55±0.10	610	37.61
18	41/0.16	1.18	0.76	2.80±0.10	610	23.85
16	26/0.254	1.49	0.76	3.10±0.10	305	15.06
14	41/0.254	1.87	0.76	3.50±0.10	305	9.46
12	65/0.254	2.36	0.76	4.0±0.10	305	6.3