


UL 1347 Irradiated PVC Insulated Wire 照射PVC线



有 AWM 1347 AWG VW-1 80°C 300V E234411 BETTER c有 AWM I A 80°C 300V FT1

PRODUCT DESCRIPTION

- Rated temperature: 105°C
Rated voltage: 300V
- Reference standard: UL Subject 758, UL1581 & CSA C22.2 No.210.2
- Tinned or bare, stranded or solid copper conductor, 30-16AWG
- Irradiated lead free PVC insulation
- Passes UL VW-1 & CSA FT1 vertical flame test

APPLICATION

For internal wiring of appliances

说明

- 额定温度：80°C
额定电压：300V
- 标准：UL758，UL1581及 CSA C22.2 No. 210.2
- 导体使用30-16AWG单根或绞合裸铜或镀锡铜线
- 照射无铅聚氯乙烯绝缘
- 通过UL VW-1及CSA FT1垂直耐燃测试

应用

用於电器设备内部连线

Conductor 导体			Insulation 绝缘		Standard Put-Up	Maximum Resistance at 20°C
AWG	NO. /mm	Dia	Nom. Thick.	Nom. Dia.	标准长度 M/Coil	最大导体电阻 Ω/km
线规	线数/线径	外径 mm	绝缘厚度 mm	外径 mm		
30	7/0.10	0.31	0.41	1.20±0.05	610	354.24
28	7/0.127	0.39	0.41	1.30±0.05	610	223.75
26	7/0.16	0.49	0.41	1.40±0.05	610	139.73
24	11/0.16	0.61	0.41	1.5±0.05	610	88.89
22	17/0.16	0.76	0.41	1.7±0.05	610	57.52
20	26/0.16	0.94	0.41	1.86±0.05	610	37.61
18	41/0.16	1.18	0.41	2.10±0.05	610	23.85
16	26/0.254	1.49	0.41	2.42±0.05	610	15.06