


UL 2969



AWM 2969 VW-1 80°C 30V E234411 BETTER C AWM I A 80°C 30V FT1

PRODUCT DESCRIPTION

- Rated temperature:80°C
Rated voltage:30V
- Reference standard:UL subject 758, UL1581 & CSA C22.2 No.210.2
- Stranded, bare or tinned copper conductor 40AWG min
- colour-coded lead free PVC or PE or PP insulation
- Tinned or bare copper stranded drain wire
- Tinned or bare copper wire braid shield available
- Lead free PVC jacket
- Passes UL VW-1& CSA FT1 vertical flame test

APPLICATION

For internal wiring and external interconnection of electronic equipment

说明

- 额定温度：80°C
额定电压：30V
- 标准：UL758，UL1581及 CSA C22.2 No. 210.2
- 导体使用绞合裸铜或镀锡铜线最小40AWG
- 无铅聚氯乙烯或聚乙烯或聚丙烯绝缘
- 镀锡或裸铜线绞合地线
- 可加上裸铜或镀锡铜线编织屏蔽
- 无铅聚氯乙烯护套
- 通过UL VW-1及CSA FT1垂直耐燃测试

应用

用於电子设备内部及外部连线

Conductor 导体		insulation 绝缘		Spiral Shield 缠绕屏蔽	Jacket 外被		Maximum Resistance at 20°C 最大导体电阻 Ω/km
AWG	NO. /mm	Nom. Thick.	Nom. Dia		Jacket thickness	Jacket. Dia	
线规	线数/线径	绝缘厚度 mm	外径 mm	No. /mm	外被厚度 mm	外径 mm	
30	7/0.10	0.153	0.65	Optional 可选	护套下的直径 是10.8或者更 小： 外被厚度 0.762	/	354.24
28	7/0.127	0.153	0.7			/	223.75
26	7/0.16	0.153	0.8			/	139.73
24	11/0.16	0.153	0.95			/	88.89
22	17/0.16	0.153	1.1			/	57.52
20	26/0.16	0.153	1.25			/	37.61
18	41/0.16	0.153	1.5			/	23.85
16	26/0.254	0.153	1.8			/	15.06