

Description


ELV688R0NS N-channel Enhancement Mode Power MOSFET

Features

- 68V, 85A
- $R_{DS(ON)}=8.0m\Omega @ V_{GS}=10V$
- Advanced Trench Technology
- Provide Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application


- Load Switch
- PWM Application
- Power management



TO-263 top view



Marking and pin Assignment



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	TUBE (PCS)	Inner BOX (PCS)	Per Carton (PCS)
ELV688R0NS	ELV688R0NS	TAPING	TO-263	13inch	2500	25000

Absolute Maximum Ratings ($T_C=25^{\circ}C$ unless otherwise specified)

Symbol	Parameter	Max.	Units
V_{DSS}	Drain-Source Voltage	68	V
V_{GSS}	Gate-Source Voltage	± 20	V
I_D	Continuous Drain Current	$T_C = 25^{\circ}C$	85
		$T_C = 100^{\circ}C$	60
I_{DM}	Pulsed Drain Current ^{note1}	340	A
E_{AS}	Single Pulsed Avalanche Energy ^{note2}	182	mJ
P_D	Power Dissipation $T_C = 25^{\circ}C$	125	W
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.0	$^{\circ}C/W$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to +150	$^{\circ}C$

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	68	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=68V, V_{GS}=0V,$	-	-	1.0	μA
I_{GSS}	Gate to Body Leakage Current	$V_{DS}=0V, V_{GS}=\pm 20V$	-	-	± 100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	-	4	V
$R_{DS(on)}$	Static Drain-Source on-Resistance <small>note3</small>	$V_{GS}=10V, I_D=40A$	-	8.0	9.1	m Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{DS}=34V, V_{GS}=0V,$ $f=1.0MHz$	-	3704	-	pF
C_{oss}	Output Capacitance		-	231	-	pF
C_{rss}	Reverse Transfer Capacitance		-	219	-	pF
Q_g	Total Gate Charge	$V_{DS}=54V, I_D=30A,$ $V_{GS}=10V$	-	80	-	nC
Q_{gs}	Gate-Source Charge		-	20	-	nC
Q_{gd}	Gate-Drain("Miller") Charge		-	31	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	$V_{DS}=34V, I_D=30A,$ $R_{GEN}=4.7\Omega, V_{GS}=10V$	-	22	-	ns
t_r	Turn-on Rise Time		-	61	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	67	-	ns
t_f	Turn-off Fall Time		-	28	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	85	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	340	A
V_{SD}	Drain to Source Diode Forward Voltage	$V_{GS}=0V, I_S=45A$	-	-	1.4	V
t_{rr}	Body Diode Reverse Recovery Time	$T_J=25^\circ\text{C}$ $I_F=30A, di/dt=100A/\mu s$	-	35	-	ns
Q_{rr}	Body Diode Reverse Recovery Charge		-	44	-	nC

- Notes: 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature
 2. EAS condition: $T_J=25^\circ\text{C}, V_{DD}=50V, V_G=10V, R_G=25\Omega, L=0.5mH, I_{AS}=27A$
 3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$

Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Case Temperature





Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case



Test Circuit




Figure1:Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveforms





Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms

Package Mechanical Data-TO-263



SYMBOL	MIN	NOM	MAX
A	4.30	4.57	4.72
A1	0	0.10	0.25
b	0.71	0.81	0.91
c	0.30	---	0.60
c2	1.17	1.27	1.37
D	8.50	---	9.35
E	9.80	---	10.45
e	2.54BSC		
H	14.70	---	15.75
L	2.00	2.30	2.74
L1	1.12	1.27	1.42
L2	---	---	1.75

Product Naming Rules

