

Draco

Non-Maintained Emergency Light for LED High Bay



Overview

Draco non-maintained LED emergency lights for LED High Bay provide a simple self-contained emergency lighting solution. The emergency lights have internal LiFePO4 battery that will provide power for a three hour duration following a cut in the power supply. The lights are available with 5 degree, 10 degree, 15 degree, 20 degree, 25 degree, 30 degree or 45 degree lens.

Features

- Non-Maintained
- Three hour rated duration
- Class I, IP65
- Built-in LED status indicator
- One second emergency conversion time
- Internal LiFePO4 battery
- Remote control for a manual test

Specifications

| | |
|---------------|--|
| Order Code | DRA05 |
| Power | 4 W (max) |
| Voltage | 220-240 Vac 50/60 Hz |
| Current | 21 mA |
| Protection | Class II, IP65 |
| Power Factor | 0.75 |
| Luminous Flux | 600lm |
| Beam Angle | 5° / 10° / 15° / 20° / 25° / 30° / 45° |
| CCT | 5000 K Day Light |
| Dimensions | As below diagram |

| | |
|---------------------------|---------------------------|
| Mounting | Product add on, Suspended |
| Connection | Wire leads |
| Emergency Conversion Time | 1 second |
| Emergency Operating Time | 3 hours |
| Battery Charging Time | 24 hours |
| Battery Design Life | 5 Years at 50°C |
| Battery Type | LiFePO4 |
| Battery Capacity | 4000 mAh |
| Battery Voltage | 6.4 V |
| Battery Code | 2IFpR27/72 4.0Ah 6.4V |
| Emergency Operation Test | Manual |
| Ambient Temperature Range | 0 to 50 °C |

Dimensions

Emergency Light



