

# Mensa

## IP65 Non-Maintained Side-Mount LED Emergency Light



### Overview

This LED Non-Maintained Emergency Light is discrete bolt-on mounted fittings that provide emergency lighting only. The light is with a standard lens design with a circular light pattern.

### Features

- Non-Maintained
- Three hour rated duration
- Class II, IP65
- Easy to install via 20mm conduit / gland entry and supplied extension tube.
- Push-wire loop-in and loop-out terminal block included
- Built-in green charging indicator
- Available in white or grey
- Built-in replaceable LiFePO4 battery
- Compatible with interior batten, anti-corrosive linear luminaire

## Specifications

Product Code	<b>MEN01-WHT</b> <b>MEN01-GRY</b>
Input Power (max)	2 W
Voltage	220-240 Vac 50/60 Hz
Input Current (max)	20 mA
Output Wattage	1.3 W
Protection	Class II, IP65
Power Factor	0.48
Luminous Flux	160 lm
Beam Angle	60 °
CCT	6000 K Day Light
Lifetime	30000 h
Warm-up time to 60%	Instant full light
LMF at Nominal Lifetime	0.75
Dimensions	135 mm x 73.5 mm x 63mm
Mounting	Product add-on, Side-mount
Ambient Temperature Range	0 to 40 °C
Emergency Conversion Time	1 second
Emergency Operating Time	3 hours
Battery Charging Time	24 hours
Battery Life	2 years
Battery Type	LiFePO4 18650
Battery Capacity	1800 mAh
Battery Voltage	3.2 V
Battery Code	LFP6501-S18
Emergency Operation Test	Manual

## Dimensions

