

# 承認書

## SPECIFICATION FOR APPROVAL

|                         |                         |
|-------------------------|-------------------------|
| ● 客戶名称                  |                         |
| ● Customer              |                         |
| ● 客戶品號                  |                         |
| ● Customer Part No.     |                         |
| ● 产品品號                  | HC-53CU25R612BJD-AB-QZX |
| ● Brightek Part No.     |                         |
| ● 产品規格描述                | 5mm 红色雾状LED             |
| ● Specification         |                         |
| ● 製錶人                   | 王清                      |
| ● Prepared By           |                         |
| ● 審核                    | 李东平                     |
| ● Checkedy              |                         |
| ● 客戶回簽                  |                         |
| ● Customer Confirmation |                         |
| ● 送样日期:                 |                         |
| ● Deliver date:         |                         |

說明: 一、謹致執事者: 茲提供敝公司產品之有關詳細規格及圖面資料, 敬請給予辦理測試認定手續。 同時敬請 送返一份附有貴公司簽認之測試認定後之樣品認定書。

We are sending you our specification and drawings for your approval. Please return to us one copy "For Approval" with your approved signatures.

二、客戶意見欄 Customer' S Proposal

☐ Approve 承認 (請於認可欄中簽名)

☐ Disagree 不同意

Reason 原因:

光字集團 中高端光电元件定制企业, 20 多年封装经验, 品质稳定, 值得信赖, 体现光的价值。

光字集团国际(香港)有限公司

GTY Group International (HK) Co., Limited

广东光宇半导体科技有限公司

工厂地址: 东莞市寮步镇松湖智谷A2 栋3 楼

东莞市弘呈光电有限公司

DongGuan Hong cheng Optoelectronics Co., Ltd.

工厂地址: 广东省东莞市樟木头镇莞樟路樟木头段15 号15 栋2108 号

ADD: Room 2108, No. 1 building, Wanhui Garden, East Guanzhang Road, Zhangmutou, Dongguan, Guangdong, China

TEL: 0769-87797616 87182291 Fax: 0769-82337396 [www.hc-led168.com](http://www.hc-led168.com)

业务联系人: 李顺阳 13925714318 (微信同号) 销售总监 企业邮箱: [sales@led-hc.com](mailto:sales@led-hc.com)



ISO 14001  
环境管理  
体系认证



ISO 9001  
环境管理  
体系认证



| 版本/版次 | 修改日期 | 修改内容 |
|-------|------|------|
|       |      |      |
|       |      |      |
|       |      |      |
|       |      |      |


**Note: this specification does not recommend using ac, such as improper operation, cause accidental death lamp or other adverse phenomenon, this company is not responsible for! Advising clients to set the current to use this product, please let us know if they set the voltage to use the product.**

## 1. overview

- \* Low power consumption
- \* Low power
- \* General equipment on the PCB board or panel
- \* with IC Supporting the use/Low current requirement

## 2. Product appearance size figure

( unit : mm )



### Note :

1 : All dimensions are in millimeters (inches).2 :

All dimension tolerance is  $\pm 0.25$ mm unless otherwise noted.

3: Specifications are subject to change without notices.

4 : This specification is for reference only for one year

### 3. parameter

#### 3.1 The limit parameter ( room temperature 25°C )

| parameter                                                     | The numerical       | Unit |
|---------------------------------------------------------------|---------------------|------|
| Dissipation power                                             | 72                  | mW   |
| Pulse current ( 1/10 work loops 0.1 millisecond pulse width ) | 100                 | mA   |
| Working current ( IF )                                        | 20                  | mA   |
| Reverse voltage ( VR )                                        | 5                   | V    |
| Experiment temperature range                                  | -20°C ~ +80°C       |      |
| Storage temperature range                                     | -20°C ~ +80°C       |      |
| Soldering temperature from the roots (4.0 mm)                 | 260°C for 5 Seconds |      |





#### Photoelectric parameters At room temperature 25°C

| Parameter           | min   | Avg   | max   | Unit | Test Condition |
|---------------------|-------|-------|-------|------|----------------|
| Luminous intensity  | 1000  | ----- | 2000  | mcd  | If=20mA        |
| Light Angle(2 θ1/2) | ----- | 100   | ----- | deg  | If=20mA        |
| Dominant(nm)        | 640   | ----- | 650   | Nm   | If=20mA        |
| Peakwave(nm)        | 660   | ----- | 700   | Nm   | If=20mA        |
| electric voltage    | 1. 8  | ----- | 2. 4  | V    | If=20mA        |
| Reverse current     |       | ----- | 5     | μA   | VR=5V          |

#### Selection Guide

| Colloid color | Chip      |                       |         |
|---------------|-----------|-----------------------|---------|
| Red diffusion | Material  | Emitting light colors | λp (nm) |
|               | GaASP/GaP | Red                   | 650     |

4、Under the condition of 25 °C electrical diagram:



**Note: this specification does not recommend using ac, such as improper operation, cause accidental death lamp or other adverse phenomenon, this company is not responsible for! Advising clients to set the current to use this product, please let us know if they set the voltage to use the product.**

## 5. Not dry glue label

P/N: Product number

VF: Forward voltage

BIN: points light


IV: Luminous intensity

WL: Color/wavelength

QTY: number

QC: Production order

## 6. packaging




The packing way : Electrostatic bag packing

Packing specification : White light color packing 500 PCS/bag, puguang 500 PCS/bag.

Pay attention to : Above belongs to the normal packing specification, if you have any special requirements according to customer requirements

## 7. The cautions of stent deformation

Stent deformation must be conducted before welding, plastic, stent bend position must be at least 3 mm at the bottom of the encapsulating resin, at the same time, avoid bent many times on the same position. When the deformation, fixed bracket, please use the right tools to avoid resin pressure. Especially not as a pivot pin connected with the resin part, so the stress within the product on light emitting structure directly into damage, lead to the change of product features and even damaged. For the same reason, in the assembly of products, the distance between welding PCB hole must be in the pin spacing of the products strictly match, as shown in the figure below :



✓ correct mounting methods

✗ Incorrect mounting methods

**Note: this specification does not recommend using ac, such as improper operation, cause accidental death lamp or other adverse phenomenon, this company is not responsible for! Advising clients to set the current to use this product, please let us know if they set the voltage to use the product.**

## 8. Reliability of the experimental project and conditions

| Test Item<br>测试项目                        | Ref. Standard<br>参考标准 | Test Conditions<br>测试条件                       | Note<br>备注 | Conclusion<br>结论 |
|------------------------------------------|-----------------------|-----------------------------------------------|------------|------------------|
| Life Test<br>常温通电                        | JESD22-A108           | Ta=25°C<br>IF=20mA                            | 1000 hrs   | 0/20             |
| Thermal Shock<br>冷热冲击                    | JESD22-A104           | -40°C±5°C 15min<br>↑↓10sec<br>100°C±5°C 15min | 100 cycle  | 0/20             |
| High Temperature Storage<br>高温存储         | JESD22-A103           | Ta=100°C±5°C                                  | 1000 hrs   | 0/20             |
| Low Temperature Storage<br>低温存储          | JESD22-A119           | Ta=-40°C±5°C                                  | 1000 hrs   | 0/20             |
| Power Temperature<br>Cycling<br>点亮高低温循环  | JESD22-A105           | 85°C±5°C 15min<br>↑↓10min<br>-40°C±5°C 15min  | 100 cycle  | 0/20             |
| High Humidity High<br>Humidity<br>高温高湿存储 | JESD22-A101           | 85°C±5°C RH=85%                               | 1000 hrs   | 0/20             |
| Wave soldering<br>波峰焊                    | JESD22-B106           | 260°C for 5 sec                               | 3 times    | 0/20             |

Criteria For Judging Damage 失效判定标准

| Test Items<br>测试项目                                    | Symbol<br>符号 | Test Condition 测<br>试条件 | Criteria For Judgement 判<br>定标准                             | Applicable project 适<br>用项目                                                  |
|-------------------------------------------------------|--------------|-------------------------|-------------------------------------------------------------|------------------------------------------------------------------------------|
| Forward Voltage 正向电<br>压                              | VF           | IF=20mA                 | $\leq \pm 30\%$                                             | Reflow<br>Temperature Cycle<br>High and Low Temperature Storage<br>Life Test |
| Luminous Flux 光通量                                     | $\phi$       | IF=20mA                 | Maintenance $\geq 70\%$ 光<br>通维持率                           |                                                                              |
| High Temperature High<br>Humidity Life Test<br>高温高湿老化 | /            | IF=20mA                 | No open circuit, short<br>circuit or flicker<br>无开路, 短路, 闪烁 | High Temperature<br>High Humidity Life Test                                  |

Note:

The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.

以上技术数据仅为产品的典型值，只作为参考（以最终双方承认的规格为准），不作为任何应用条件及应用方式的保证。

## 9. ESD protective

LED is a semiconductor device, the static sensitive, especially for white, green, blue, purple LED to make efforts to prevent electrostatic generation and eliminate static electricity.

### 9.1 The generation of static electricity

a. Friction: in daily life, any two objects of different material contact after the separation, can produce static, and the one of the most common method of generation of static electricity, is the electrification. The insulation material, the better, the easier the electrification. In addition, any two objects of different material contact again after separation, also can produce static electricity.

b. Induction: in view of the conductive material, because electrons can flow freely in its surface, such as to be put in the electric field, due to the same, opposites attract, the positive and negative ions will move, can produce electric charge on the surface.

c. Conduction: in view of the conductive material, because electrons can flow freely in surface, such as contact with a charged object, the charge transfer will occur.

### 9.2 The dangers of static electricity on the LED :

a. For the moment's electric field or electric current produced by the heat, the LED local injury.

b. Because of destruction of the electric field or current LED insulation layer, the device will not work (destroyed) characterized by death lamp.

### 9.3 Electrostatic protection and measures to eliminate

For the entire process (production, testing, packaging, etc.) all employees in direct contact with the LED to measures to prevent and eliminate static electricity, mainly :

- a. Laying anti-static workshop floor and well grounded.
- b. Workbench for ESD workstation, production machines grounding is good.
- c. Operators wear anti-static clothing, anti-static hand ring, gloves or foot ring.
- d. Application of ion fan, the welding electric grounding measures.
- e. Packing with antistatic materials.