



TEST REPORT
IEC 60598-2-1
Luminaires
Part 2: Particular requirements
Section 1: Fixed general purpose luminaires

Report Number.....: LCSB05064166S

Date of issue.....: November 27, 2024

Total number of pages.....: 73 pages

Name of Testing Laboratory preparing the Report.....: Shenzhen Southern LCS Compliance Testing Co., Ltd.

Applicant's name.....: Sundopt LED Lighting Co., Ltd.

Address.....: Bldg 8-6#, TongFuYu Industrial Park Ai Qun Rd Shiyan Town Baoan District Shenzhen, Guangdong 518108

Test specification:

Standard.....: IEC 60598-2-1:2020 used in conjunction with IEC 60598-1:2020

Test procedure.....: CE-LVD

Non-standard test method.....: N/A

TRF template used.....: IECEE OD-2020-F1:2021, Ed.1.4

Test Report Form No.....: IEC60598_2_1I

Test Report Form(s) Originator.....: Intertek Semko AB

Master TRF.....: Dated 2022-04-14

Copyright © 2021 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved IECEE Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report.



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Test item description.....:	LED LUMINAIRES	
Trade Mark.....:	N/A	
Manufacturer.....:	Sundopt LED Lighting Co., Ltd.	
Address.....:	Bldg 8-6#, TongFuYu Industrial Park Ai Qun Rd Shiyan Town Baoan District Shenzhen, Guangdong 518108	
Model/Type reference.....:	See model list on page 5	
Ratings.....:	See model list on page 5	
☒ Testing Laboratory:		
Testing location/ address.....:	Shenzhen Southern LCS Compliance Testing Co., Ltd. Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China	
Tested by.....:	Eli Yang (Engineer)	<i>Eli Yang</i>
Check by.....:	Torres He (Director)	<i>Torres He</i>
Approved by.....:	Jesse Liu (Manager)	<i>Jesse Liu</i>
List of Attachments (including a total number of pages in each attachment): Attachment No. 1: European group differences and national differences according to EN IEC 60598-2-1:2021 used in conjunction with EN IEC 60598-1:2021+A11:2022. Attachment No. 2: Report IEC/EN IEC 62031. Attachment No. 3: Report IEC TR 62778. Attachment No. 4: Photo documentation.		
Summary of testing:		
Tests performed (name of test and test clause): IEC 60598-2-1:2020 IEC 60598-1:2020 IEC TR 62778: 2014 IEC 62031:2018 IEC 62493:2015+A1:2022	Testing location: Shenzhen Southern LCS Compliance Testing Co., Ltd. Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China	
Summary of compliance with National Differences:		
List of countries addressed ☒ The product fulfils the requirements of European Group differences EN IEC 60598-2-1:2021; EN IEC 60598-1:2021+A11:2022; EN 62493:2015+A1:2022; EN IEC 62031:2020+A11:2021		



**Copy of marking plate:**

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

LED LUMINAIRES**Model: NCWP-1508025-DD****220-240V~, 50/60Hz, 80W****ta. 40°C****Sundopt LED Lighting Co., Ltd.****Bldg 8-6#, TongFuYu Industrial Park Ai Qun Rd Shiyan Town****Baoan District Shenzhen, Guangdong 518108****The products can be interconnected,
interconnection current is less 2A****Importer: xxxxxxxx****Address: xxxxxxxx****Remarks:**

1. Representative markings of NCWP-1508025-DD, markings of all models are identical except for the model name and rating.
2. Height of CE mark at least 5mm, height of WEEE symbol should not less than 7mm, height of other marks at least 5mm, height of letters and numerals at least 2mm.



Shenzhen Southern LCS Compliance Testing Co., Ltd.

Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China

Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test item particulars..... :									
Classification of installation and use.....: Fixed general purpose luminaires									
Supply Connection.....: Supply cord									
Protection Class.....: Class I									
Degree of Protection..... : IP20									
Possible test case verdicts:									
- test case does not apply to the test object..... : N/A									
- test object does meet the requirement..... : P (Pass)									
- test object does not meet the requirement..... : F (Fail)									
Testing..... :									
Date of receipt of test item..... : 2024-11-07									
Date (s) of performance of tests..... : 2024-11-07 ~ 2024-11-26									
General remarks:									
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Clause numbers with "*" were not within the scope of CNAS recognition. Clause numbers between brackets refer to clauses in IEC/EN IEC 60598-1. The general information of applicant and manufacturer (such as the name and address), product name, model/type reference, trademark and other similar information contained in this report are all provided by the applicant, the laboratory is not responsible for verifying its authenticity. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. According to the EU directives which have been aligned with EU NLF (new legislative framework), both of manufacturer and importer's name and address shall be affixed on the product or, where that is not possible, on its packaging or in a document accompanying the product before the product is placed on the EU market. Modified Information <table border="1" style="width: 100%;"><thead><tr><th>Version</th><th>Report No.</th><th>Revision Date</th><th>Summary</th></tr></thead><tbody><tr><td>V1.0</td><td>LCSB05064166S</td><td>/</td><td>Original Version</td></tr></tbody></table>		Version	Report No.	Revision Date	Summary	V1.0	LCSB05064166S	/	Original Version
Version	Report No.	Revision Date	Summary						
V1.0	LCSB05064166S	/	Original Version						
Manufacturer's Declaration per sub-clause 4.2.5 of IECIEE 02:									
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....:	☐ Yes ☒ Not applicable								
When differences exist; they shall be identified in the General product information section.									
Name and address of factory (ies)..... : Same as manufacturer									



**General product information:**

- All models are the same except model name, power and size, structure, circuit scheme (principle, PCB).
- The products can be interconnected, interconnection current is less 2A.
- Unless otherwise specified, the model NCWP-1508025-DD was chosen as representative model to perform all test, NCP1-1205025-ND-R, NCP1-1506030-VD-M, NCWP-1508025-VD, NCWP-1508025-ND and was chosen to perform partial test.

Model List:

For all models: 220-240V~, 50/60Hz, Class I, IP20, ta 40°C.

Model No.	Power (W)	LED driver	Size (L*W*Hmm)	Maximum number of interconnection(pcs)
NCWP-1206020-ND	60W	BK-CWL060-B1650A	1125*108*46mm	7
NCWP-1206020-VD	60W	BK-KHL060-1650Am or BK-EML060-A1650AMV	1125*108*46mm	7
NCWP-1206020-DD	60W	BK-DAL060-B1650A	1125*108*46mm	7
NCWP-1508025-ND	80W	BK-CWL080-B2000A	1445*108*46mm	5
NCWP-1508025-VD	80W	BK-KML080-B2000AMV	1445*108*46mm	5
NCWP-1508025-DD	80W	BK-DBL080S-A2000ADP	1445*108*46mm	5
NCP1-1205025-ND-R	50W	BK-CWL060-B1300A or BK-CWL060-B1650A	1126*46*80mm	8
NCP1-1205025-ND-RM				
NCP1-1205025-ND-M				
NCP1-1205025-VD-R	50W	BK-KHL050-1300Am or BK-KHL060-1650Am	1126*46*80mm	8
NCP1-1205025-VD-RM				
NCP1-1205025-VD-M				
NCP1-1205025-DD-R	50W	BK-DAL050-1300Ad or BK-DAL060-1650Ad	1126*46*80mm	8
NCP1-1205025-DD-RM				
NCP1-1205025-DD-M				
NCP1-1205025-PD-R	50W	BK-DAL050-1300Ad or BK-DAL060-1650Ad	1126*46*80mm	8
NCP1-1205025-PD-RM				
NCP1-1205025-PD-M				
NCP1-1506030-ND-R	60W	BK-CWL060-B1650A	1446*46*80mm	7
NCP1-1506030-ND-RM				
NCP1-1506030-ND-M				
NCP1-1506030-VD-R	60W	BK-KHL060-1650Am	1446*46*80mm	7
NCP1-1506030-VD-RM				



Shenzhen Southern LCS Compliance Testing Co., Ltd.

Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China

Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



NCP1-1506030-VD-M					
NCP1-1506030-DD-R	60W	BK-DAL060-1650Ad or BK-DAL080-B2000Ad	1446*46*80mm	7	
NCP1-1506030-DD-RM	60W	BK-DAL060-1650Ad or BK-DAL080-B2000Ad	1446*46*80mm	7	
NCP1-1506030-DD-M					
NCP1-1506030-PD-R	60W	BK-CWL060-B1650A or BK-DAL080-B2000Ad	1446*46*80mm	7	
NCP1-1506030-PD-RM					
NCP1-1506030-PD-M					





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.4 (0)	GENERAL TEST REQUIREMENTS		P
1.4 (0.3)	More sections applicable.....:	Yes ☐ No ☒ Section/s:	—
1.4 (0.5)	Components	(see Annex 1)	—
1.4 (0.7)	Information for luminaire design in light sources standards		—
1.4 (0.7.2)	Light source safety standard	IEC/EN IEC 62031	—
	Luminaire design in the light source safety standard		P

1.5 (2)	CLASSIFICATION OF LUMINAIRES		P
1.5 (2.2)	Type of protection	Class I	P
1.5 (2.3)	Degree of protection.....:	IP20	—
1.5 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces.....:	Yes ☒ No ☐	—
1.5 (2.5)	Luminaire for normal use	Yes ☒ No ☐	—
	Luminaire for rough service	Yes ☐ No ☒	—

1.6 (3)	MARKING		P
1.6 (3.2)	Mandatory markings		P
	Position of the marking		P
	Format of symbols/text		P
1.6 (3.3)	Additional information		P
	Language of instructions	English	P
1.6 (3.3.1)	Combination luminaires		N/A
1.6 (3.3.2)	Nominal frequency in Hz	50/60Hz	P
1.6 (3.3.3)	Operating temperature		N/A
1.6 (3.3.5)	Wiring diagram		N/A
1.6 (3.3.6)	Special conditions		N/A
1.6 (3.3.7)	Metal halide lamp luminaire – warning		N/A
1.6 (3.3.8)	Limitation for semi-luminaires		N/A
1.6 (3.3.9)	Power factor and supply current		P
1.6 (3.3.10)	Suitability for use indoors		N/A
1.6 (3.3.11)	Luminaires with remote control		N/A
1.6 (3.3.12)	Clip-mounted luminaire – warning		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.6 (3.3.13)	Specifications of protective shields		N/A
1.6 (3.3.14)	Symbol for nature of supply	~	P
1.6 (3.3.15)	Rated current of socket outlet		N/A
1.6 (3.3.16)	Rough service luminaire		N/A
1.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	Type Y	P
1.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
1.6 (3.3.19)	Protective conductor current in instruction if applicable		N/A
1.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
1.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided	Non-user replaceable	P
1.6 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
1.6 (3.3.23)	Luminaires without control gear provided with necessary information for selection of appropriate component		N/A
1.6 (3.3.24)	If not supplied with terminal block, information on the packaging		P
1.6 (3.3.25)	Luminaires employing light sources emitting UV on mains wiring, information provided		N/A
1.6 (3.3.26)	Wall mounted luminaire using external flexible cable or cord longer than 0.3 m, information provided		N/A
1.6 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P

1.7 (4)	CONSTRUCTION		P
1.7 (4.2)	Components replaceable without difficulty		P
1.7 (4.3)	Wireways smooth and free from sharp edges		P
1.7 (4.4)	Lamp holders		N/A
1.7 (4.4.1)	Integral lamp holder		N/A
1.7 (4.4.2)	Wiring connection		N/A
1.7 (4.4.3)	Lamp holder for end- to-end mounting		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7 (4.4.4)	Positioning		N/A
	- pressure test (N)		—
	After test the lamp holder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lamp holder the lamp holder has not moved from its position and show no permanent deformation		N/A
	- bending test (N)		—
	After test the lamp holder has not moved from its position and show no permanent deformation		N/A
1.7 (4.4.5)	Peak pulse voltage		N/A
1.7 (4.4.6)	Centre contact		N/A
1.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
1.7 (4.4.8)	Lamp connectors		N/A
1.7 (4.4.9)	Caps and bases correctly used		N/A
1.7 (4.4.10)	Light source for lamp holder or connection according IEC 60061 not connected another way		N/A
1.7 (4.5)	Starter holders		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
1.7 (4.6)	Terminal blocks		P
	Tails		P
	Unsecured blocks		P
1.7 (4.7)	Terminals and supply connections		P
1.7 (4.7.1)	Contact to metal parts		P
1.7 (4.7.2)	Test 8 mm live conductor		P
	Test 8 mm earth conductor		P
1.7 (4.7.3)	Terminals for supply conductors		P
1.7 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.6.2		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.3.2.3 and 15.6.3.2.4		N/A
1.7 (4.7.4)	Terminals other than supply connection		N/A
1.7 (4.7.5)	Heat-resistant wiring/sleeves		N/A
1.7 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
1.7 (4.8)	Switches		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
1.7 (4.9)	Insulating lining and sleeves		P
1.7 (4.9.1)	Retainment		P
	Method of fixing.....:		P
1.7 (4.9.2)	Insulated linings and sleeves:		N/A
	Resistant to a temperature > 20 °C to the wire temperature or		N/A
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C).....:		N/A
1.7 (4.10)	Double or reinforced insulation		N/A
1.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N/A
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
1.7 (4.10.2)	Assembly gaps:		N/A
	- not coincidental		N/A
	- no straight access with test probe		N/A
1.7 (4.10.3)	Retainment of insulation:		N/A
	- fixed		N/A
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lamp holder		N/A
1.7 (4.10.4)	Protective impedance device		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Basic and supplementary insulation bridged by resistor(s) or appropriate capacitor		N/A
	Double or reinforced insulation bridged by at least two separate resistors in series or appropriate capacitor(s)		N/A
	Capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.2 of IEC 60065		N/A
1.7 (4.11)	Electrical connections and current-carrying parts		P
1.7 (4.11.1)	Contact pressure		P
1.7 (4.11.2)	Screws:		N/A
	- self-tapping screws		N/A
	- thread-cutting screws		N/A
1.7 (4.11.3)	Screw locking:		P
	- spring washer		P
	- rivets		N/A
1.7 (4.11.4)	Material of current-carrying parts		P
1.7 (4.11.5)	No contact to wood or mounting surface		P
1.7 (4.11.6)	Electro-mechanical contact systems		N/A
1.7 (4.12)	Screws and connections (mechanical) and glands		P
1.7 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		N/A
	Torque test: torque (Nm); part.....:	Fixed Enclosure: 0.6Nm	P
	Torque test: torque (Nm); part.....:	Fixed Terminal block: 0.6Nm	P
	Torque test: torque (Nm); part.....:	Fixed Cord anchorage: 0.5Nm	P
	Torque test: torque (Nm); part.....:	Fixed Earth wire: 0.5Nm	P
	Torque test: torque (Nm); part.....:	Fixed LED driver: 0.6Nm	P
	Torque test: torque (Nm); part.....:	Fixed DC PCB board: 0.5Nm	P
	Torque test: torque (Nm); part.....:	Fixed LED cover: 0.5Nm	P
1.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		P
1.7 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm).....:		N/A
	- lamp holder; torque (Nm).....:		N/A
	- push-button switches; torque 0,8 Nm.....:		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7 (4.12.5)	Screwed glands; force (Nm)..... :		N/A
1.7 (4.13)	Mechanical strength		P
1.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)..... :		N/A
	- other parts; energy (Nm)..... :	Enclosure: 0.35Nm	P
	1) live parts		P
	2) linings		P
	3) protection		P
	4) covers		P
1.7 (4.13.2)	Metal parts have adequate mechanical strength		P
1.7 (4.13.3)	Straight test finger		P
1.7 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
1.7 (4.13.6)	Tumbling barrel		N/A
1.7 (4.14)	Suspensions, fixings and means of adjusting		P
1.7 (4.14.1)	Mechanical load:		P
	A) four times the weight	4*max.4.41Kg	P
	B) torque 2,5 Nm		N/A
	C) bracket arm; bending moment (Nm)..... :		N/A
	D) load track- mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		N/A
	Metal rod. diameter (mm)		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
1.7 (4.14.2)	Load to flexible cables		N/A
	Mass (kg)		—
	Stress in conductors (N/mm ²)		N/A
	Mass (kg) of semi-luminaire		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Bending moment (Nm) of semi-luminaire		N/A
1.7 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles.....		N/A
	- strands broken.....		N/A
	- electric strength test afterwards		N/A
1.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
1.7 (4.14.5)	Guide pulleys		N/A
1.7 (4.14.6)	Strain on socket-outlets		N/A
1.7 (4.15)	Flammable materials		P
	- glow-wire test 650°C.....	See Test Table 1.15 (13.3.2)	P
	- spacing ≥ 30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
1.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
1.7 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear.....	(compliance with Section 12)	N/A
	Provided with adaptor for a track meet the requirements for direct mounting on normally flammable surfaces		N/A
1.7 (4.16.1)	Lamp control gear spacing:		N/A
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
1.7 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
1.7 (4.17)	Drain holes		N/A
	Clearance at least 5 mm		N/A
1.7 (4.18)	Resistance to corrosion		P
1.7 (4.18.1)	- rust-resistance		N/A
1.7 (4.18.2)	- season cracking in copper		P
1.7 (4.18.3)	- corrosion of aluminium		N/A
1.7 (4.19)	Igniters compatible with ballast		N/A
1.7 (4.20)	Rough service vibration		N/A
1.7 (4.21)	Protective shield		N/A
1.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
1.7 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
1.7 (4.21.3)	No direct path		N/A
1.7 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment.....:	See Test Table 1.15 (13.3.2)	N/A
1.7 (4.22)	Attachments to lamps not cause overheating or damage		N/A
1.7 (4.23)	Semi-luminaires comply Class II		N/A
1.7 (4.24)	Photobiological hazards		P
1.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A
1.7 (4.24.2)	Retinal blue light hazard		P
	Class of risk group assessed according to IEC/TR 62778	RG1	—
	Luminaires with E_{thr} :		N/A
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2...:		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
1.7 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
1.7 (4.26)	Short-circuit protection		N/A
1.7 (4.26.1)	Adequate means of uninsulated accessible SELV / PELV parts		N/A
1.7 (4.26.2)	Short-circuit test with test chain according 4.26.3:		N/A
	Supply source ES1 PSE		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
1.7 (4.27)	Terminal blocks with integrated screwless protective earthing contacts		N/A
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
1.7 (4.28)	Fixing of thermal sensing control		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material ($^{\circ}\text{C}$)		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
1.7 (4.29)	Luminaires with non-replaceable light source		N/A
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A
1.7 (4.30)	Luminaires with non-user replaceable light source		P



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test		Verdict
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	At least one fixing means requiring use of tool		P
1.7 (4.31)	Insulation between circuits		P
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
1.7 (4.31.1)	SELV or PELV circuits		P
	Used SELV/PELV source		P
	Voltage $\leq$ ELV		P
	Insulating of SELV/PELV circuits from LV supply		P
	Insulating of SELV/PELV circuits from other non SELV/PELV circuits		N/A
	Insulating of SELV/PELV circuits from FELV		N/A
	Insulating of SELV/PELV circuits from other SELV/PELV circuits		N/A
	SELV/PELV circuits insulated from accessible parts according Table X.1		P
	Plugs not able to make any electrical contact with socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
1.7 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage $\leq$ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to make any electrical contact with socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets have protective conductor contact		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		N/A
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
1.7 (4.32)	Overvoltage protective devices		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
1.7 (4.33)	Luminaire powered via information technology communication cabling		N/A
	Requirements for Class III luminaire		N/A
	Rated voltage within the range of ES1 and does not exceed maximum voltage of used connector		N/A
	Luminaire does not create any hazard from overvoltage	(see Annex 2)	N/A
1.7 (4.34)	Electromagnetic fields (EMF)		P
	No harmful electromagnetic fields		P
1.7 (4.35)	Protection against moving fan blades		N/A
	Test with a standard test finger		N/A
	Test with test probe acc. to Figure 13 (IEC 61032) for portable luminaire		N/A
	Blades rounded with radius ≥ 0.5 mm and:		N/A
	-hardness less than D60 Shore		N/A
	-peripheral speed less than 15 m/s		N/A
	-input power of fan ≤ 2 W at rated voltage		N/A
1.7 (4.36)	Track-mounted luminaires		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Test in accordance with Annex A of IEC60570:2003/AMD2:2019		N/A
--	--	--	-----

1.8 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
1.8 (11.2.1)	Impulse withstand category (Normal category II)	Category II ☒ Category III ☐	—
	Category III according Annex U		N/A
	Protected against pollution, reduced creepage and clearance according Annex P of IEC 61347-1		N/A
1.8 (11.2.2)	Creepage distances for frequency up to 30 kHz	See Test Table 1.8 (11.2) I	P
	Creepage distances for frequency over 30 kHz:		N/A
	- Controlgear marked with $\hat{U}_{OUT}$ and f_{UOUT} according IEC 61347-1, clause 7.1, item w	See Test Table 1.8 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 1.8 (11.2) II	N/A
1.8 (11.2.3)	Clearances for frequency up to 30 kHz	See Test Table 1.8 (11.2) I	P
	Clearances distances for frequency over 30 kHz:		N/A
	- Controlgear marked with U_P	See Test Table 1.8 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 1.8 (11.2) II	N/A

1.9 (7)	PROVISION FOR EARTHING		P
1.9 (7.2.1 + 7.2.3)	Accessible metal parts		P
	Metal parts in contact with supporting surface		P
	Resistance < 0,5 Ω:	Max. 0.075 Ω	P
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a grove		N/A
	Protective earth makes contact first		P
	Terminal blocks with integrated screwless protective earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
1.9 (7.2.2 + 7.2.3)	Protective earth continuity in joints, etc.		P
1.9 (7.2.4)	Locking of clamping means		P





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance with 4.7.3		P
1.9 (7.2.5)	Protective earth terminal integral part of connector socket		N/A
1.9 (7.2.6)	Protective earth terminal adjacent to mains terminals		N/A
1.9 (7.2.7)	Electrolytic corrosion of the protective earth terminal		N/A
1.9 (7.2.8)	Material of protective earth terminal		P
	Contact surface bare metal		P
1.9 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
1.9 (7.2.11)	Protective earthing core coloured green-yellow		P
	Length of protective earthing conductor		P
1.9 (7.2.12)	PELV circuit connected to protective earth for functional purpose		N/A

1.10 (14)	SCREW TERMINALS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire	(see Annex 3)	N/A

1.10 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		P
	Separately approved; component list.....:	(see Annex 1)	P
	Part of the luminaire.....:	(see Annex 4)	N/A

1.11 (5)	EXTERNAL AND INTERNAL WIRING		P*
1.11 (5.2)	Supply connection and external wiring		P
1.11 (5.2.1)	Means of connection.....:	Supply cord	P
	Outdoor luminaire has not PVC insulated external wiring if not Class III or SELV/PELV circuits ≤ 25 V AC/60 V DC/25 V peak interrupted DC voltage with frequency 10Hz -200 Hz or protected from outdoor environment		N/A
1.11 (5.2.2)	Type of cable.....:	SEE ANNEX 1	P
	Nominal cross-sectional area (mm ²).....:	SEE ANNEX 1	P
	Cables equal to IEC 60227 or IEC 60245		N/A
1.11 (5.2.3)	Type of attachment, X, Y or Z		P
1.11 (5.2.5)	Type Z not connected to screws		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.11 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		P
1.11 (5.2.7)	Cable entries through rigid material have rounded edges		P
1.11 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
1.11 (5.2.9)	Locking of screwed bushings		N/A
1.11 (5.2.10)	Cord anchorage:		N/A
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
1.11 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
1.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		P
1.11 (5.2.10.3)	Tests:		N/A
	- impossible to push cable; unsafe		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- pull test: 25 times; pull (N)..... :		N/A
	- torque test: torque (Nm)..... :		N/A
	- displacement ≤ 2 mm		N/A
	- no movement of conductors		N/A
	- no damage of cable or cord		N/A
	- function independent of electrical connection		N/A
1.11 (5.2.10.4)	Luminaire with/ designed for use with supply cord with maximum current of 2A:		P
	- Ordinary Class III luminaire supplied with SELV ≤ 25 V RMS/60V DC		N/A
	- Ordinary Class III luminaire supplied with PELV ≤ 12 V RMS/30V DC		N/A
	- Other than ordinary Class III luminaire supplied with voltage ≤ 12 V RMS/30V DC		N/A
	Pull test of 30N		P
1.11 (5.2.11)	External wiring passing into luminaire		N/A
1.11 (5.2.12)	Looping-in terminals		N/A
1.11 (5.2.13)	Wire ends not tinned		P
	Wire ends tinned: no cold flow		N/A
1.11 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
1.11 (5.2.15)	Connectors for Class III luminaires (IEC 60603 or IEC 62680)		N/A
1.11 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Appliance inlet or connector systems (IEC 61984)		N/A
1.11 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
1.11 (5.2.18)	Used plug in accordance with		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- IEC 60083		N/A
	- other standard		N/A
1.11 (5.3)	Internal wiring		P
1.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		P
	- not delivered/ mounting instruction		N/A
	- factory assembled		N/A
	- socket outlet loaded (A)..... :		N/A
	- temperatures..... :	(see Annex 2)	P
	Green- yellow for protective earth only		P
1.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		N/A
	Cross-sectional area (mm ²)..... :		N/A
	Insulation thickness (mm) :		N/A
	Extra insulation added where necessary		N/A
1.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		P
	Cross-sectional area (mm ²)..... :		P
1.11 (5.3.1.3)	Double or reinforced insulation for class II		N/A
1.11 (5.3.1.4)	Conductors without insulation		N/A
1.11 (5.3.1.5)	SELV/PELV current-carrying parts		P
1.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
1.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		N/A
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		P
1.11 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- cables with protective sheath		N/A
1.11 (5.3.4)	Joints and junctions effectively insulated		N/A
1.11 (5.3.5)	Strain on internal wiring		P
1.11 (5.3.6)	Wire carriers		N/A
1.11 (5.3.7)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		P
1.11 (5.4)	Test to determine suitability of conductors having a reduced cross-sectional area		N/A
	Under test the temperature of the luminaire wiring insulation not exceed the limits stated in Table 12.2	(see Annex 2)	N/A
	No damage to luminaire wiring after test		N/A

1.12 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
1.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		N/A
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		P
	Lamp and starter holders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high-pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
1.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
1.12 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- required insulation from live parts in compliance with Table X.1		N/A
	- glass protective shields not used as supplementary insulation		N/A
1.12 (8.2.3.b)	BC lamp holder of metal in class I luminaires shall be connected to protective earth		N/A
1.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V).....:		N/A
	- voltage under load/ no-load DC (V).....:		N/A
	- interrupted DC voltage (V)		N/A
	- touch current if applicable (mA)		N/A
	One conductive part insulated if required		N/A
	Other than ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V).....:		N/A
	- voltage under load/ no-load DC (V).....:		N/A
	- interrupted DC voltage (V)		N/A
	Class III luminaire only for connection to SELV/PELV		N/A
1.12 (8.2.3.d)	PELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V).....:		N/A
	- voltage under load/ no-load DC (V).....:		N/A
	Other than ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V).....:		N/A
	- voltage under load/ no-load DC (V).....:		N/A
	One pole insulated if required		N/A
1.12 (8.2.4)	Portable luminaire has protection independent of supporting surface		N/A
1.12 (8.2.5)	Compliance with the standard test finger or relevant probe		P
1.12 (8.2.6)	Covers reliably secured		P
1.12 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection	0V	P





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N/A
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A
1.13 (12)	ENDURANCE TEST AND THERMAL TEST		P
1.13 (-)	If IP > IP 20 relevant test of (12.4), (12.5), (12.6) and (12.7) after (9.2) before (9.3) as specified in 1.14		—
1.13 (12.2)	Selection of lamps and ballasts		—
	Lamp used according Annex B	(Lamp used see Annex 2)	—
	Control gear if separate and not supplied	(Control gear used see Annex 2)	—
1.13 (12.3)	Endurance test		P
	a) mounting- position	As normal used	—
	b) test temperature ($^{\circ}$ C).....	40 $^{\circ}$ C+10 $^{\circ}$ C	—
	c) total duration (h)	240h	—
	d) supply voltage (V).....	1.1x240V~	—
	d) if not equipped with control gear, constant voltage/current (V) or (A)		—
1.13 (12.3.1d)	d) Class III luminaires powered via information technology communication cable:		N/A
	- voltage under normal operation (V).....		—
	- voltage under abnormal operation (V).....		—
	e) luminaire ceases to operate		—
	f) luminaire with constant light output function		N/A
1.13 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N/A
	- marking legible		P
	- no cracks, deformation etc.		P
1.13 (12.4)	Thermal test (normal operation)	(see Annex 2)	P
1.13 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.13 (12.6)	Thermal test (failed lamp control gear condition):		N/A
1.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions.....		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un		N/A
	- calculated mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
1.13 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions.....		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
1.13 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
1.13 (12.7.1)	Luminaire without temperature sensing control		N/A
1.13 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N/A
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- calculated temperature of fixing point/exposed part (°C):.....:		—
	Ball-pressure test.....:	See Test Table 1.15 (13.2.1)	N/A
1.13 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions.....:		—
	- measured winding temperature (°C): at 1,1 Un.....:		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....:		—
	- calculated temperature of fixing point/exposed part (°C):.....:		—
	Ball-pressure test.....:	See Test Table 1.15 (13.2.1)	N/A
1.13 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions.....:		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
1.13 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link.....:	Yes ☐ No ☐	—
	- manual reset cut-out.....:	Yes ☐ No ☐	—
	- auto reset cut-out.....:	Yes ☐ No ☐	—
	- case of abnormal conditions.....:		—
	- highest measured temperature of fixing point/exposed part (°C):.....:		—
	Ball-pressure test.....:	See Test Table 1.15 (13.2.1)	N/A

1.14 (9)	RESISTANCE TO DUST AND MOISTURE		P
1.14 (-)	If IP > IP 20 the order of tests as specified in clause 1.12		P
1.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		P
	- classification according to IP.....:	IP20	—
	- mounting position during test.....:	Normal installation	—
	- fixing screws tightened; torque (Nm).....:	2/3 torque of cl4.12.1	—
	- tests according to clauses.....:	Clause 9.2.0	—





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		N/A
	b) no talcum in dust-tight luminaire		N/A
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	c.1) For luminaires without drain holes – no water entry		N/A
	c.2) For luminaires with drain holes – no hazardous water entry		N/A
	d) no water in watertight, pressure watertight, high pressure and temperature water jet-proof or high pressure and cold water jet-proof luminaire		N/A
	e) no contact with live parts (IP 2X)		P
	e) no entry into enclosure (IP 3X and IP 4X)		N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N/A
	f) no trace of water on part of lamp requiring protection from splashing water		N/A
	g) no damage of protective shield or glass envelope		N/A
1.14 (9.3)	Humidity test 48 h	25°C, 93%RH	P

1.15 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
1.15 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø	Metal foil	—
	Insulation resistance (MΩ):		P
	SELV/PELV:		P
	- between current-carrying parts of different polarity:		N/A
	- between current-carrying parts and mounting surface.....	>100 MΩ	P
	- between current-carrying parts and metal parts of the luminaire.....	>100 MΩ	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....		N/A
	- Insulation bushings as described in Section 5		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Other than SELV/PELV:		P
	- between live parts of different polarity..... :	>100 MΩ	P
	- between live parts and mounting surface..... :	>100 MΩ	P
	- between live parts and metal parts..... :	>100 MΩ	P
	- between live parts of different polarity through action of a switch..... :		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5		N/A
1.15 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Test voltage (V):		P
	SELV/PELV:		P
	- between current-carrying parts of different polarity:		N/A
	- between current-carrying parts and mounting surface..... :	500Vac	P
	- between current-carrying parts and metal parts of the luminaire..... :	500Vac	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV/PELV:		P
	- between live parts of different polarity..... :	1480Vac	P
	- between live parts and mounting surface..... :	1480Vac	P
	- between live parts and metal parts..... :	1480Vac	P
	- between live parts of different polarity through action of a switch..... :		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N/A
	- Insulation bushings as described in Section 5		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.15 (10.3)	Touch current (mA).....:		N/A
	Protective conductor current (mA).....:	Max. 0.063mA	P

1.16 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		P
1.16 (13.2.1)	Ball-pressure test.....:	See Test Table 1.16 (13.2.1)	P
1.16 (13.3.1)	Needle-flame test (10 s).....:	See Test Table 1.16 (13.3.1)	P
1.16 (13.3.2)	Glow-wire test (650°C).....:	See Test Table 1.16 (13.3.2)	P
1.16 (13.4)	Proof tracking test (IEC 60112).....:	See Test Table 1.16 (13.4)	N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.8 (11.2)	TABLE I: Creepage distances and clearances						P
	Minimum distances (mm) for a.c. up to 30 kHz sinusoidal voltages						P
	Applicable part of IEC 60598-1 Table 11.1.A*, 11.1.B* and 11.2*						P
	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	B	see below	1.5	Table 11.1.B	see below	2.5	Table 11.1.A
Distance 2:	B	2.7	1.5	Table 11.1.B	2.7	2.5	Table 11.1.A
Working voltage (V)..... :					Max. 240V for input		—
PTI..... :					< 600 ☒ ≥ 600 ☐		—
Pulse voltage or U_P if applicable (kV) :					--		—
Supplementary information:							
Distance 1:The voltage is not more than SELV 60 V d.c., No creepage distance and clearance values are specified for working voltages below 60 V d.c. as the test voltage of electric strength is considered sufficient.							
Distance 2: Between current-carrying parts and mounting surface.							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.16 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics			P
Allowed impression diameter (mm):		2		—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
Plastic lens	See Annex 1	86.7	1.5	
Terminal block	See Annex 1	125	1.0	
Closed-end connector	See Annex 1	125	1.1	
Interconnecting terminal	See Annex 1	125	1.4	
DC PCB board	See Annex 1	125	0.7	
Supplementary information:				

1.16 (13.3.1)	TABLE: Needle-flame test				P
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Terminal block	See Annex 1	10s	No	0s	P
Closed-end connector	See Annex 1	10s	No	0s	P
Interconnecting terminal	See Annex 1	10s	No	0s	P
DC PCB board	See Annex 1	10s	No	0s	P
Supplementary information:					

1.16 (13.3.2)	TABLE: Resistance to heat and fire - Glow wire tests				P
Object/ Part No./ Material	Manufacturer/ trademark	GWT (°C) : 650			Verdict
		t _E (s)	t _I (s)	t _R (s)	
Plastic lens	See Annex 1	0	0	0	P
Ignition of the specified layer placed underneath the test specimen (Yes/No).....					No
Supplementary information:					

1.16 (13.4)	TABLE: Proof tracking test			N/A
Test voltage PTI		175 V	—	
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens		Verdict





IEC 60598-2-1					
Clause	Requirement + Test			Result - Remark	Verdict
--	--	--	--	--	--
Supplementary information:					



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1	TABLE: Critical components information					P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity1)
For models with size of wide is 46mm						
Supply cord	B	Dongguan City Xin Hailin Wire and Cable Technology Co., Ltd.	H05VV-F	5x0.75mm ² 3x0.75mm ²	DIN EN 50525-2-11 EN 50525-2-11	VDE 40043059
Input wire of LED Driver and Earth wire	B	3F Electronics Industry Corp., Qifurui Industry Park	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40050652
- Alt.	D	Dong Guan Sheng Pai Electric Wire & Cable Co Ltd,	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40053466
- Alt.	D	Shenzhen Dongju Wire & CableCo., Ltd.	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40031065
Fiberglass sleeving	C	HENG HUI CHANG INSULATION MATERIAL COLTD	HHC-03	600V. 200°C	EN IEC 60598-2-1 EN IEC 60598-1	UL E240604
Heat-shrinkable tube	C	GUANGZHOU K AIHENG NEW MATERIALCO LTD	k-2	600V; 125°C	EN IEC 60598-2-1 EN IEC 60598-1	ULE321827
Quick connector Input side and interconnect ion terminal)	C	Cixi kongtone Electronics Technology Co.,Ltd	TCK3.5 TCZ3.5	130°C 250V, 16A	EN60998-01	CE B-S200831456 R1
LED driver	B	DONGGUAN BOKE LED DRIVERS CO., LTD.	BK-CWL060-B1300A	Input: 200-240V~, 50/60Hz, 0.38A Max. Output: DC28-40V, 1.3A, 60W Max., ta50°C, tc90°C, SELV	EN 61347-2-13:2014/A1: 2017EN 61347-1:2015/A1:2 021	No. N8A 089086 0498 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-CWL060-B1650A	Input: 200-240V~, 0/50/60Hz, 0.38A Max. Output: DC28-38V, 1.65A, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1: 2017EN 61347-1:2015/A1:2 021	No. N8A 089086 0498 Rev.00



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
LED driver	B	BOKE Drivers Co., Ltd.	BK-KHL050-1300Am	Input: 200-240V~, 0/50/60Hz, 0.29A Max. Output: DC 24-40V, 1300mA, 52W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No. N8A 089086 0132 Rev.02
LED driver	B	BOKE Drivers Co., Ltd.	BK-KHL060-1650Am	Input: 200-240V~, 0/50/60Hz, 0.37A Max. Output: DC 24-38V, 1650mA, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No. N8A 089086 0132 Rev.02
LED driver	B	BOKE Drivers Co., Ltd.	BK-DAL050-B1300Ad	Input: 200-240V~, 0/50/60Hz, 0.29A Max. Output: DC 6-38V, 1300mA, 50W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No.N8A 089086 0392 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-DAL060-B1650Ad	Input: 200-240V~, 0/50/60Hz, 0.38A Max. Output: DC 6-38V, 1650mA, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No.N8A 089086 0392 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-DAL080-B2000Ad	Input: 200-240V~, 0/50/60Hz, 0.47A Max. Output: DC 6-40V, 2000mA, 80W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No.N8A 089086 0392 Rev.00
Output wire of LED driver	B	GUANGDONG HAERKN NEW ENERGY CO LTD	1332	20AWG, 105°C, 300V	--	UL E300956
- Alt.	D	DONGGUAN ZHIHE ELECTRICAL CABLE TECH CO LTD	1332	20AWG, 105°C, 300V	--	UL E258239
Output connector (orange)	B	Guangdong Ojun Technology Co., Ltd.	OJ-602B-3P	250V, 6A	DIN EN 60998	CE 4370808.01A OC
LED	C	SHENZHEN SUCCESS	ODW-003	V-0, 130°C	--	UL E319737





IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
PCBLower lighting Surface and Connecting PCB		STONE TECHNOLOGIES CO LTD				
- Alt.	D	FENGSHUN JIAFENG ELECTRICAL CO LTD	JF-D	V-0, 130°C	--	UL E493538
- Alt.	D	Shenzhen Huayu Circuits Co Ltd	HY-D	V-0, 130°C	--	UL E465882
LED Lower lighting surface	B	Wenzhou JKUN Connector Co Ltd	L001	250V/6A	--	UL E473017
- Alt.	D	ZHEJIANG LIANHE ELECTRONIC CO LTD	2060-LHE	250V/6A	--	UL E364711
Quick connector	C	ZHEJIANG LIANHE ELECTRONIC CO LTD	PH	300V, 2A	--	UL E364711
- Alt.	D	ZHEJIANG KUAILI ELECTRONICS CO LTD	PH2000	300V, 2A	--	UL E307817
LED PCB Lower lighting surface	C	FENGSHUN JIAFENG ELECTRICAL CO LTD	JF-AL	V-0, 130°C, metal base	--	UL E493538
- Alt.	D	Shenzhen Huayu Circuits Co Ltd	HY-MH	V-0, 130°C, metal base	--	UL E465882
- Alt.	D	Hefengxin Electronics Co Ltd	HFX-01	V-0, 90°C, metal base	--	UL E489916
LED	C	EBRIGHT SHENZHEN OPTO-ELECTRONIC CO.,LTD	2835	White: IF: 100mA, VF: 2.7-3.3V	IEC TR 62778	Test with appliance
LED	C	EBRIGHT SHENZHEN OPTO-ELECTRONIC CO.,LTD	2835	White: IF: 100mA, VF: 8.5--9.0V	IEC TR 62778	Test with appliance
Plastic lens Lower lighting surface	C	TEIJIN POLYCARBONATE CHINA LTD	L-1225	94-V2	--	UL E245526
Reflection plastic Lower lighting surface	C	TEIJIN POLYCARBONATE CHINA LTD	L-1225	94-V2	--	UL E245526
Grille cover Lower lighting surface	C	TEIJIN POLYCARBONATE CHINA LTD	L-1225	94-V2	--	UL E245526



Shenzhen Southern LCS Compliance Testing Co., Ltd.

Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China

Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
Plastic Lens upper lighting surface	C	CHI MEI CORPORATION	CM-205	94-HB	--	UL E56070
For models with size of wide is 108mm						
Supply cord	B	Dongguan City Xin Hailin Wire and Cable Technology Co., Ltd.	H05VV-F	5x0.75mm ² 3x0.75mm ²	DIN EN 50525-2-11	VDE 40043059
Input wire of LED Driver and interconnect on wire	B	3F Electronics Industry Corp., Qifurui Industry Park	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40050652
- Alt.	B	Dong Guan Sheng Pai Electric Wire & Cable Co Ltd,	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40053466
- Alt.	B	Shenzhen Dongju Wire & CableCo., Ltd.	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40031065
Earth wire	B	3F Electronics Industry Corp., Qifurui Industry Park	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40050652
- Alt.	B	Dong Guan Sheng Pai Electric Wire & Cable Co Ltd,	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40053466
- Alt.	B	Shenzhen Dongju Wire & CableCo., Ltd.	H05V-K	0.75mm ²	DIN EN 50525-2-31	VDE 40031065
Connector	B	Degson Electronics Co. Ltd.,	DG280J DG280K	450V~, 24A	DIN EN 61984	VDE 40030768
- Alt.	D	BJB GmbH & Co. KG,	Serie(s) 48.281 Serie(s) 48.271	400V~, 16A	DIN EN 61984	VDE 40007917





IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
LED driver	B	BOKE Drivers Co., Ltd.	BK-CWL060-B1650A	Input: 200-240V~, 0/50/60Hz, 0.38A Max. Output: DC28-38V, 1.65A, 62.7W Max, ta60°C, tc90°C, SELV	EN 61347-2-13 EN 61347-1	No. N8A 089086 0498 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-KHL060-1650Am	Input: 200-240V~, 0/50/60Hz, 0.37A Max. Output: DC 24-38V, 1650mA, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13 EN 61347-1	No. N8A 089086 0132 Rev.02
LED driver	B	BOKE Drivers Co., Ltd.	BK-EML060-A1650AMV	Input: 200-240V~, 0/50/60Hz, 0.36A Max. Output: DC 12-42V, 1650mA, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13 EN 61347-1	No.N8A 089086 0488 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-DAL060-B1650Ad	Input: 200-240V~, 0/50/60Hz, 0.38A Max. Output: DC6-38V, 1.65A, 62.7W, ta60°C, tc90°C, SELV	EN 61347-2-13:2014/A1:2017EN 61347-1:2015/A1:2021	No.N8A 089086 0392 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-CWL080-B2000A	Input: 200-240V~, 0/50/60Hz, 0.45A Max. Output: DC28-40V, 2A, 80W Max, ta50°C, tc95°C, SELV	EN 61347-2-13 EN 61347-1	No. N8A 089086 0498 Rev.00
LED driver	B	BOKE Drivers Co., Ltd.	BK-EML080-B2000AMV	Input: 200-240V~, 0/50/60Hz, 0.456A Max. Output: DC 12-40V, 2000mA, 80W, ta50°C, tc85°C, SELV	EN 61347-2-13 EN 61347-1	No.N8A 089086 0488 Rev.00





IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
LED driver	B	BOKE Drivers Co., Ltd.	BK-DBL080S-A2000ADP	Input: 200-240V~, 0/50/60Hz, 0.5A Max. Output: DC 12-40V, 2A, 80W, ta50°C, tc80°C, SELV	EN 61347-2-13 EN 61347-1	No.U6 089086 0452 Rev.00
Output wire of LED driver	C	GUANGDONG HAERKN NEW ENERGY CO LTD	1332	20AWG, 105°C, 300V	--	UL E300956
- Alt.	D	DONGGUAN ZHIHE ELECTRICAL CABLE TECH CO LTD	1332	20AWG, 105°C, 300V	--	UL E258239
Output connector (orange)	C	Guangdong Ojun Technology Co., Ltd.	OJ-602B-3P	250V, 6A	DIN EN 60998	CE 4370808.01A OC
PCB	C	SHENZHEN SUCCESS STONE TECHNOLOGIES CO LTD	ODW-003	V-0, 130°C	--	UL E319737
- Alt.	D	FENGSHUN JIAFENG ELECTRICAL CO LTD	JF-D	V-0, 130°C	--	UL E493538
- Alt.	D	Shenzhen Huayu Circuits Co Ltd	HY-D	V-0, 130°C	--	UL E465882
Quick connector (beige)	C	Wenzhou JKUN Connector Co Ltd	L001	250V/6A	--	UL E473017
Alt.	D	ZHEJIANG LIANHE ELECTRONIC CO LTD	2060-LHE	250V/6A	--	UL E364711
Quick connector (white)	C	ZHEJIANG LIANHE ELECTRONIC CO LTD	PH	300V, 2A	--	UL E364711
- Alt.	D	ZHEJIANG KUAILI ELECTRONICS CO LTD	PH2000	300V, 2A	--	UL E307817
LED PCB	C	FENGSHUN JIAFENG ELECTRICAL CO LTD	JF-AL	V-0, 130°C,	--	UL E493538
- Alt.	D	Shenzhen Huayu Circuits Co Ltd	HY-MH	V-0, 130°C,	--	UL E465882
- Alt.	D	Hefengxin Electronics Co Ltd	HFX-01	V-0, 130°C,	--	UL E489916





IEC 60598-2-1						
Clause	Requirement + Test			Result - Remark		Verdict
LED	C	EBRIGHT SHENZHEN OPTO-ELECTRONIC CO.,LTD	2835	White: IF: 100mA, VF: 8.5--9.0V	IEC TR 62778 EN 62031	Test with appliance
Plastic Component	C	TEIJIN POLYCARBONATE CHINA LTD	L-1225	94-V2	--	UL E245526
Plastic Component upper lighting surface	C	CHI MEI CORPORATION	CM-205	94-HB	--	UL E56070

Supplementary information:

¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039.

The codes above have the following meaning:

- A- The component is replaceable with another one, also certified, with equivalent characteristics
- B- The component is replaceable if authorised by the test house
- C- Integrated component tested together with the appliance
- D- Alternative component



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12		P
	Type reference.....:	NCWP-1508025-DD	—
	Lamp used.....:	LED module	—
	Lamp control gear used.....:	BK-DBL080S-A2000ADP	—
	Mounting position of luminaire.....:	As normal use	—
	Supply wattage (W)	393.6W	—
	Supply current (A)	1.6A	—
	Calculated power factor.....:	0.967	—
	Temperatures in test 1 - 4 below are corrected for ta (°C)	40°C	—
	- abnormal operating mode.....:	--	—
1.13 (12.4)	- test 1: rated voltage	--	—
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current	1.06x240V~	—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:	--	—
	Through wiring or looping-in wiring loaded by a current of A during the test	Max. 1.6A	—
1.13 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current or 130/150% of rated input voltage.....:	--	—

Temperature measurements (°C)

Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Supply cord	40	--	51.8	--	90	--	--
Through the wire	40	--	73.7	--	90	--	--
Input terminals	40	--	49.2	--	Ref.	--	--
tc of LED driver	40	--	75.3	--	90	--	--
Internal wire of LED	40	--	65.3	--	90	--	--
Closed-end connector	40	--	41.7	--	Ref.	--	--
LED PCB	40	--	68.6	--	130	--	--
Interconnecting terminal	40	--	80.5	--	Ref.	--	--
DC PCB board	40	--	53.4	--	Ref.	--	--



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1							
Clause	Requirement + Test			Result - Remark			Verdict
Plastic lens	40	--	57.7	--	Ref.	--	--
Mounting surface	40	--	46.1	--	90	--	--
Supplementary information:							





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12		P
	Type reference.....:	NCP1-1506030-VD-M	—
	Lamp used.....:	LED module	—
	Lamp control gear used.....:	BK-KHL060-1650Am	—
	Mounting position of luminaire.....:	As normal use	—
	Supply wattage (W)	422.1W	—
	Supply current (A)	1.75A	—
	Calculated power factor.....:	0.947	—
	Temperatures in test 1 - 4 below are corrected for ta (°C)	40°C	—
	- abnormal operating mode.....:	--	—
1.13 (12.4)	- test 1: rated voltage	--	—
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current	1.06x240V~	—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:	--	—
	Through wiring or looping-in wiring loaded by a current of A during the test	Max. 1.75A	—
1.13 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current or 130/150% of rated input voltage.....:	--	—

Temperature measurements (°C)

Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Supply cord	40	--	53.9	--	90	--	--
Through the wire	40	--	81.3	--	90	--	--
Input terminals	40	--	51.3	--	Ref.	--	--
tc of LED driver	40	--	76.9	--	90	--	--
Internal wire of LED	40	--	71.9	--	90	--	--
DC connector	40	--	56.3	--	Ref.	--	--
LED PCB	40	--	62.1	--	Ref.	--	--
Interconnecting terminal	40	--	81.2	--	Ref.	--	--
DC PCB board	40	--	51.8	--	Ref.	--	--



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District,
Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1							
Clause	Requirement + Test			Result - Remark			Verdict
Plastic lens	40	--	61.7	--	Ref.	--	--
Mounting surface	40	--	47.3	--	90	--	--
Supplementary information:							





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12		P				
	Type reference.....:	NCP1-1205025-ND-R	—				
	Lamp used.....:	LED module	—				
	Lamp control gear used.....:	BK-CWL060-B1300A	—				
	Mounting position of luminaire..... :	As normal use	—				
	Supply wattage (W)	408.8W	—				
	Supply current (A)	1.69A	—				
	Calculated power factor.....:	0.948	—				
	Temperatures in test 1 - 4 below are corrected for ta (°C)	40°C	—				
	- abnormal operating mode.....:	--	—				
1.13 (12.4)	- test 1: rated voltage	--	—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current	1.06x240V~	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:	--	—				
	Through wiring or looping-in wiring loaded by a current of A during the test	Max. 1.69A	—				
1.13 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current or 130/150% of rated input voltage..... :	--	—				
Temperature measurements (°C)							
Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
tc of LED driver	40	--	73.4	--	90	--	--
Mounting surface	40	--	48.1	--	90	--	--
Supplementary information:							





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12			P			
	Type reference.....:	NCWP-1508025-VD	—				
	Lamp used.....:	LED module	—				
	Lamp control gear used.....:	BK-KML080-B2000AMV	—				
	Mounting position of luminaire.....:	As normal use	—				
	Supply wattage (W)	397.7W	—				
	Supply current (A)	1.62A	—				
	Calculated power factor.....:	0.965	—				
	Temperatures in test 1 - 4 below are corrected for ta (°C)	40°C	—				
	- abnormal operating mode.....:	--	—				
1.13 (12.4)	- test 1: rated voltage	--	—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current	1.06x240V~	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:	--	—				
	Through wiring or looping-in wiring loaded by a current of A during the test	Max.1.62A	—				
1.13 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current or 130/150% of rated input voltage.....:	--	—				
Temperature measurements (°C)							
Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
tc of LED driver	40	--	78.8	--	90	--	--
Mounting surface	40	--	46.8	--	90	--	--
Supplementary information:							





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12		P				
	Type reference.....:	NCWP-1508025-ND	—				
	Lamp used.....:	LED module	—				
	Lamp control gear used.....:	BK-CWL080-B2000A	—				
	Mounting position of luminaire..... :	As normal use	—				
	Supply wattage (W)	390.3W	—				
	Supply current (A)	1.59A	—				
	Calculated power factor.....:	0.965	—				
	Temperatures in test 1 - 4 below are corrected for ta (°C)	40°C	—				
	- abnormal operating mode.....:	--	—				
1.13 (12.4)	- test 1: rated voltage	--	—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current	1.06x240V~	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:	--	—				
	Through wiring or looping-in wiring loaded by a current of A during the test	Max.1.59A	—				
1.13 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current or 130/150% of rated input voltage..... :	--	—				
Temperature measurements (°C)							
Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
tc of LED driver	40	--	74.6	--	85	--	--
Mounting surface	40	--	47.7	--	90	--	--
Supplementary information:							





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 3	Screw terminals (part of the luminaire)		N/A
(14)	SCREW TERMINALS		N/A
(14.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm ²)..... :		—
(14.3.3)	Conductor space (mm)..... :		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread)..... :	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm)..... :		N/A
	Torque (Nm)..... :		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N)..... :		N/A
(14.4.8)	Without undue damage		N/A

ANNEX 4	Screwless terminals (part of the luminaire)		N/A
(15)	SCREWLESS TERMINALS		N/A
(15.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples).....:		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples).....:		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples).....:		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
(15.6)	Terminals and connections for external wiring		N/A
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)		N/A
(15.6.3)	Electrical tests		N/A





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	TABLE: Contact resistance test / Heating tests										N/A
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
Supplementary information:											

	ANNEX 5: EMF test result according to IEC/EN 62493	P
4	LIMITS	P
4.1	General	P





IEC 60598-2-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Comply with Van der Hoofden test limit in 4.2.3 or inherently compliant in 4.2.2 and pass assessment procedure for intentional radiators in 4.3		P
4.2	Unintentional radiating part of lighting equipment		P
4.2.2	Lighting equipment deemed to comply with the Van der Hoofden test without testing		P
	1) electronic controlgear	Yes ☐ No ☒	—
	2) incandescent-lamp technology	Yes ☐ No ☒	—
	3) LED-light-source technology	Yes ☒ No ☐	—
	4) OLED-light-source technology	Yes ☐ No ☒	—
	5) high-pressure discharge lamp	Yes ☐ No ☒	—
	6) low-pressure discharge lamp technologies with exposure distance ≥ 50 cm	Yes ☐ No ☒	—
	7) independent auxiliary	Yes ☐ No ☒	—
	Not fulfil any of 1-7 above subject to 4.2.3		—
4.2.3	Applications of limits		N/A
	Not fulfil any of 1-7 in 4.2.2 but the compliance factor F is ≤ 1		N/A
4.3	Intentional radiating part of lighting equipment		N/A
	Comply with one of methods in Clause 7 if intentional radiator		N/A
6	MEASUREMENT PROCEDURE FOR THE VAN DER HOOFDEN TEST		N/A
6.1	General		N/A
	Measurements carried out under conditions according Clause 6.1 – 6.6	See Table 6	N/A
7	ASSESSMENT PROCEDURE INTENTIONAL RADIATORS		N/A
7.2	Low-power exclusion method		N/A
7.2.1	Input $P_{\text{int,rad}}$:		—
	Exclusion level P_{max}:		—
	Input power $P_{\text{int,rad}} < \text{exclusion level } P_{\text{max}}$		N/A
7.3	Application of the EMF product standard for body worn-equipment		N/A
	If not Clause 7.2 is met and expose distance ≤ 0.05 m, comply with IEC 62209-2		N/A
7.4	Application of the EMF product standard for base stations		N/A





IEC 60598-2-1					
Clause	Requirement + Test			Result - Remark	Verdict
	If not Clause 7.2 is met and if intentional radiator is base station, comply with IEC 62232				N/A
7.5	Application of another EMF standard				N/A
	If not Clause 7.2 is met and if intentional radiator cannot be considered as in Clause 7.3 or 7.4, comply with IEC 62311				N/A

6	TABLE: Measurement results with Van der Hoofden test head					N/A
Location of EUT		Test model	Measuring distance	Result(F)	Limit(F)	Verdict
Reference Annex B of IEC/EN 62493:2015+A1:2022		--	--	--	≤1.0	N/A





Attachment No.1

IEC 60598_2_11-ATTACHMENT

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

ATTACHMENT TO TEST REPORT IEC 60598-2-1
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Luminaires

Part 2: Particular requirements

Section 1: Fixed general purpose luminaires

Differences according to..... : EN IEC 60598-2-1:2021 used in conjunction with
EN IEC 60598-1:2021+A11:2022

	CENELEC COMMON MODIFICATIONS (EN)	P
--	--	---

1.7 (4)	CONSTRUCTION	N/A
1.7 (4.11.6)	Electro-mechanical contact systems	N/A

1.11 (5)	EXTERNAL AND INTERNAL WIRING	N/A
1.11 (5.2.2)	Cables equal to EN 50525	N/A
	Replace table 5.1 – Supply cord	N/A

1.13 (12)	ENDURANCE TESTS AND THERMAL TESTS	P
1.13 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring	P
ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)	N/A
(3.3)	DK: power supply cords of class I luminaires with label	N/A
(4.5.1)	DK: socket-outlets	N/A
(5.2.1)	CY, DK, FI, GB: type of plug	N/A

ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)	N/A
(4 & 5)	FR: Shuttered socket-outlets 10/16A	N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.1

IEC 60598_2_11-ATTACHMENT

Clause	Requirement + Test	Result - Remark	Verdict
	FR: Safety requirements for high buildings (Decree of 30 December 2011 on safety regulations for the construction of high-rise buildings and their protection against fire and panic risks; Section VIII; Article GH 48, Lighting) Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	GB: Requirements according to United Kingdom Building Regulation		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.2

IEC/EN IEC 62031 LED modules for general lighting - Safety specifications			
Clause	Requirement + Test	Result - Remark	Verdict
4.2	Classification		---
	Built-in.....:	Yes ☐ No ☒	—
	Independent.....:	Yes ☐ No ☒	—
	Integral.....:	Yes ☒ No ☐	—
4.6	Independent modules comply with requirements in IEC 60598-1:2020		N/A
4.8	Modules with integrated controlgear providing SELV comply with requirements according to IEC 61347-1:2015/AMD1:2017 clause L.5 to L.11.	(see Annex 1)	N/A
6	Marking		N/A
6.2	Contents of marking for built-in and for independent LED modules		N/A
6.3	Location of marking for built-in LED modules		N/A
6.4	Location of marking for independent LED modules		N/A
6.5	Marking of integral LED modules		P
6.6	Durability and legibility of marking		N/A
7	Terminals		N/A
8 (9)	EARTHING		N/A
9 (10)	Protection against accidental contact with live parts		N/A
10 (11)	Moisture resistance and insulation		P
11 (12)	Electric strength		P*
12 (14)	Fault conditions		P
12.1	Fault conditions according to IEC 61347-1, Clause 14		P
12.2	Overpower condition	No damage	P
14 (15)	Construction		P
- (15.1)	Wood, cotton, silk, paper and similar fibrous material		P
	Wood, cotton, silk, paper and similar fibrous material not used as insulation		P
- (15.2)	Printed circuits		P
	Printed circuits used as internal connections complies with clause 14		P



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.2

IEC/EN IEC 62031 LED modules for general lighting - Safety specifications			
Clause	Requirement + Test	Result - Remark	Verdict
15 (16)	Creepage distances and clearances		N/A
16 (17)	Screws, current-carrying parts and connections		N/A
17 (18)	Resistance to heat, fire and tracking		N/A
18	Resistance to corrosion		N/A
20	Heat management		N/A
22	Photobiological safety		P
22.1	UV radiation		N/A
22.2	Blue light hazard		P
	Assessed according to IEC TR 62778		P
22.3	Infrared radiation		N/A



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District,
Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.3

IEC TR 62778 Photobiological safety of lamps and lamp systems			
Clause	Requirement + Test	Result - Remark	Verdict

Table 4.6 (4.24)		Spectroradiometric measurement (IEC TR 62778: 2014)		--
	Measurement performed on:	Luminaire		--
	Model number.....	NCWP-1508025-DD		--
	Test voltage (V).....	240V~		--
	Test current (mA).....	--		--
	Test frequency (Hz).....	50		--
	Measurement distance.....	☒ 20 cm ☐ ... cm		--
	Source size	☒ Non-small ☐ Small : mm		--
	Field of view	☐ 100 mrad ☒ 11 mrad ☐ 1,7 mrad (for small sources)		--
Item	Symbol	Units	Result	Risk Group
Correlated colour temperature	CCT	K	--	--
x/y colour coordinates	--	--	--	--
Blue light hazard radiance	L _B	W/(m ² •sr ¹)	958	☐ RG0: <100 ☒ RG1: <10000 ☐ RG2: <4000000
Blue light hazard irradiance	E _B	W/m ²	--	--
Luminance	L	cd/m ²	--	--
Illuminance	E	lx	--	--
Supplementary information: Bottom light source.				



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.3

IEC TR 62778 Photobiological safety of lamps and lamp systems			
Clause	Requirement + Test	Result - Remark	Verdict

Table 4.6 (4.24)	Spectroradiometric measurement (IEC TR 62778: 2014)			--
	Measurement performed on:	Luminaire		--
	Model number.....	NCWP-1508025-DD		--
	Test voltage (V).....	240V~		--
	Test current (mA).....	--		--
	Test frequency (Hz).....	50		--
	Measurement distance.....	☒ 20 cm ☐ ... cm		--
	Source size	☒ Non-small ☐ Small : mm		--
	Field of view	☐ 100 mrad ☒ 11 mrad ☐ 1,7 mrad (for small sources)		--
Item	Symbol	Units	Result	Risk Group
Correlated colour temperature	CCT	K	--	--
x/y colour coordinates	--	--	--	--
Blue light hazard radiance	L _B	W/(m ² •sr ¹)	1057	☐ RG0: <100 ☒ RG1: <10000 ☐ RG2: <4000000
Blue light hazard irradiance	E _B	W/m ²	--	--
Luminance	L	cd/m ²	--	--
Illuminance	E	lx	--	--
Supplementary information: Top light source.				



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.4

Photo Documentation

Model: NCWP-1508025-DD




Photo 1




Photo 2



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.4

Photo Documentation




Photo 3




Photo 4





Attachment No.4

Photo Documentation



Photo 5



Photo 6



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.4

Photo Documentation



Photo 7




Photo 8





Attachment No.4

Photo Documentation




Photo 9




Photo 10





Attachment No.4

Photo Documentation



Photo 11




Photo 12





Attachment No.4

Photo Documentation




Photo 13




Photo 14



Photo 15



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.4

Photo Documentation




Photo 16



Photo 17





Attachment No.4

Photo Documentation



Photo 18



Photo 19



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Attachment No.4

Photo Documentation




Photo 20




Photo 21





Attachment No.4

Photo Documentation




Photo 22




Photo 23





Attachment No.4

Photo Documentation



Photo 24




Photo 25





Attachment No.4

Photo Documentation




Photo 26




Photo 27





Attachment No.4

Photo Documentation




Photo 28




Photo 29





Attachment No.4

Photo Documentation



Photo 30




Photo 31

-----End of Test Report-----



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Add: Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: +(86) 0755-29871520 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity