

GINTEC P3

P3 is the first cost-effective handheld controller launched by GINTEC, pursuing the ultimate quality assurance and cost control.

KEYFEATURES

- ◆ **5.5 Inch**
Wide-angle high-brightness display
- ◆ **1080*1920 Resolution**
- ◆ **800 nits**
Clear visibility even in intense sunlight
- ◆ **8 Cores 2.0G**
- ◆ **4+64G RAM**
- ◆ **Corning 3th Generation**
1.1mm glass
- ◆ **Full lamination process**
- ◆ **9000mAh high-capacity battery**
- ◆ **IP67**
- ◆ **Android 11**
- ◆ **Camera 13MP**



SPECIFICATIONS

Platform	MT8768
RF frequency band	Global Version: GSM: 850/900/1800/1900 WCDMA: B1/B2/B4/B5/B8 LTE-TDD: B38/B39/B40/B41 LTE-FDD: B1/B2/B3/B4/B5/B7/B8/ B12/B13/B17/B20/B28
Operating system	Android 11
Touchscreen	1.1mm Corning Gorilla Glass cover Supports glove mode Raindrop resistant Fingerprint resistant
System memory	4GB LPDDR+64
Display module	5.5 FHD 1080*1920 OPTIONAL
Bluetooth	BT2.1+EDR/3.0/4.1LE/4.2/5.0 BLE
WIFI	802.11 a/b/g/n/ac
NFC	Supported
GPS	GPS, GLONASS, BeiDou tri-system single-frequency Single-point positioning, no raw data output
SIM	Single Nano SIM
T-Flash	Supports MicroSD expansion, up to 512GB maximum
Gravity sensor	Supported
Ambient light sensor	Supported
Proximity sensor	Supported
Compass	Supported
Gyroscope	Supported
OTG	Supported
Front camera	Not applicable
Rear camera	13MP with autofocus
Flashlight	Supported
Speaker	100dB loudspeaker
Indicator light	1
Buttons	27 keys Alphanumeric keys + function keys LED backlight (main keyboard keys)
USB	Type C
Charger	18W PD2.0 5V/3A 9V/2A
Battery	9000mAh
Overall dimensions	230*87*22.7mm
Weight	430g
Operating temperature	-30°C to +60°C
Storage temperature	-40°C to +80°C
Waterproof and dustproof rating	IP67
Humidity	5%-95%, non-condensing
Drop resistance	1.2-meter drop resistant



Room401-403, Building A02, No. 83, Kaiyuan Avenue, Huangpu District,
Guangzhou, Guangdong, China



www.gintec.cn



overseas@gintec.cn

info@gintec.cn